


NEON-NT1615-J

Specifications

| | |
|-------------------|----------------------------------|
| Type | Neon Flex |
| Dimension | W16mm. X H15mm. |
| Lifetime | 50,000Hours@25° |
| Operating temp | Ta=25 °C to 60 °C (Tc max=65 °C) |
| Finish | UV & Flame-resistant PVC |
| Accessories | Aluminum profile |
| Mounting | Concealed in slot |
| IP Rating | IP67 |
| Power | 10W/m |
| Beam Angle | 130° |
| Color Temperature | 3000K |
| Color Rendering | ≥ 90 |
| Rate Lumen Output | 700lm |
| Bin/Step | 5-Step Macadam ellipse |
| Bending | Top |
| Supply voltage | DC24V |



Unit: mm
Cross section


Accessories



Stainless Steel Clip

Aluminum Clip

Aluminum Profile



Bendable Stainless Steel Clip

Direction Optional




Front Cable Entry:
The cable could be hidden in all directions by the flexible design.

Side Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.

Bottom Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.

Photometric Data



Cable size / Max distance

| 0.5mm ² | 0.75mm ² | 1.0mm ² | 1.5mm ² | 2.5mm ² |
|--------------------|---------------------|--------------------|--------------------|--------------------|
| 20AWG | 18AWG | 17AWG | 15AWG | 13AWG |
| | 4m | 8m | 10m | 18m |