


NEON-NT1615-J-DW

Specifications

Type	Neon Flex
Dimension	W16mm. X H15mm.
Lifetime	50,000Hours@25°
Operating temp	Ta=25 °C to 60 °C (Tc max=65 °C)
Finish	UV & Flame-resistant PVC
Accessories	Aluminum profile
Mounting	Concealed in slot
IP Rating	IP67
Power	15W/m
Beam Angle	130°
Color Temperature	CCT Dynamic white 2200K-6000K
Color Rendering	≥ 90
Rate Lumen Output	850lm
Bin/Step	5-Step Macadam ellipse
Bending	Top
Supply voltage	DC24V




Accessories



Stainless Steel Clip

Aluminum Clip

Aluminum Profile



Bendable Stainless Steel Clip

Direction Optional




Front Cable Entry:
The cable could be hidden in all directions by the flexible design.

Side Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.

Bottom Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.

Photometric Data



Cable size / Max distance

0.5mm ²	0.75mm ²	1.0mm ²	1.5mm ²	2.5mm ²
20AWG	18AWG	17AWG	15AWG	13AWG
	4m	8m	10m	18m