


NEON-NT1615-J-IP68

Specifications

Type	Neon Flex
Dimension	W16mm. X H15mm.
Lifetime	50,000Hours@25°
Operating temp	Ta=25 °C to 60 °C (Tc max=65 °C)
Finish	UV & Flame-resistant PVC
Accessories	Aluminum Profile
Mounting	Concealed in slot
IP Rating	IP68
Power	10W/m
Beam Angle	130°
Color Temperature	3000K
Color Rendering	≥ 90
Rate Lumen Output	375lm
Bin/Step	5-Step Macadam ellipse
Bending	Top
Supply voltage	DC24V



Unit: mm
Cross section

Accessories



Stainless Steel Clip



Aluminum profile



⚠ not applicable to swimming pools



Transparent PC profile



Direction Optional



Front Cable Entry:
The cable could be hidden in all directions by the flexible design.




Side Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.



Bottom Cable Entry:
The cable could be perfectly hidden to achieve seamless light connection.

Photometric Data



Cable size / Max distance

0.5mm ²	0.75mm ²	1.0mm ²	1.5mm ²	2.5mm ²
20AWG	18AWG	17AWG	15AWG	13AWG
	4m	8m	10m	18m